

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

## 1. Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Bilacryl PU D34 / D44  
Unique Formula Identifier : G520-E0YH-F001-EPHR

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

Coatings and paints, fillers, putties, thinners. The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier :** MONOPOL AG  
**Street/P.O.Box :** Oberrohrdorferstrasse 51  
**Country code/Postal code/Town/City :** 5442 Fislisbach  
**Telephone :** +41 56 484 77 77  
**Telefax :** +41 56 484 77 99  
**Contact :** info@monopol-colors.ch

### 1.4 Emergency telephone number

+41 44 251 51 51

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.  
STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.  
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.  
Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

##### Signal word

Warning

##### Hazard components for labelling

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC ; CAS No. : 64742-95-6  
N-BUTYL ACETATE ; CAS No. : 123-86-4

##### Hazard statements

H226 Flammable liquid and vapour.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P312 Call a POISON CENTER/doctor/... if you feel unwell.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

P370+P378 In case of fire: Use dry sand, dry powder, or alcohol-resistant foam to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container to hazardous waste

### Additional information

P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges.

### 2.3 Other hazards

#### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 3. Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6

Weight fraction :  $\geq 15 - < 20$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

2-METHOXY-1-METHYLETHYL ACETATE ; REACH No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226  
Substance with a common (EC) occupational exposure limit value.

MIXED XYLENE ; REACH No. : 01-2119488216-32-xxxx ; EC No. : 905-588-0

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; REACH No. : 01-2119472146-39 ; EC No. : 265-150-3; CAS No. : 64742-48-9

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC ; REACH No. : 01-2119455851-35 ; EC No. : 265-199-0; CAS No. : 64742-95-6

Weight fraction :  $\geq 1 - < 5$  %  
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### 3.3 Additional information

Paint material, solventborne

## 4. First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### Following inhalation

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

Remove casualty to fresh air and keep warm and at rest. Keep at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice.

### In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

### After eye contact

Remove contact lenses, keep eyelids open. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

### Following ingestion

Call a physician in any case! Keep at rest. Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

None

## 5. Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>) Water spray jet

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use suitable breathing apparatus.

### 5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. See protective measures under point 7 and 8.

### 6.2 Environmental precautions

Cover drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean with detergents. Avoid solvent cleaners.

### 6.4 Reference to other sections

None

## 7. Handling and storage

### 7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

be kept away. Take precautionary measures against static discharges. Wear anti-static footwear and clothing It is recommended to design all work processes always so that the following is excluded: Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Comply with the health and safety at work laws. For personal protection see Section 8. Respiratory protection necessary at: spray application

## Protective measures

### Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

## 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Always close containers tightly after the removal of product. Never use pressure to empty container. Only allow access to authorised staff. Keep away from sources of ignition - No smoking. Always close containers tightly after the removal of product. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

### Hints on joint storage

Storage class (TRGS 510) ( D ) : 3

### Do not store together with

Do not store together with Acid alkali Oxidizing agent

### Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from sources of ignition - No smoking. Keep in a cool, well-ventilated place. Keep in a cool, well-ventilated place. Comply with the health and safety at work laws.

## 7.3 Specific end use(s)

None

## 8. Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : MAK ( CH )

Limit value : 240 mg/m<sup>3</sup> / 50 ml/m<sup>3</sup>

Remark : SSC

Version : 22.02.2021

Limit value type (country of origin) : STEL ( CH )

Limit value : 720 mg/m<sup>3</sup> / 150 ml/m<sup>3</sup>

Remark : SSC

Version : 22.02.2021

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 62 ppm / 300 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

Version : 06.11.2015

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : MAK ( CH )

Limit value : 275 mg/m<sup>3</sup> / 50 ml/m<sup>3</sup>

Remark : SSC

Version : 22.02.2021

Limit value type (country of origin) : STEL ( CH )

Limit value : 275 mg/m<sup>3</sup> / 50 ml/m<sup>3</sup>

Remark : SSC

Version : 22.02.2021

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 270 mg/m<sup>3</sup>

Peak limitation : 1(I)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Bilacryl PU D34 / D44  
**Revision date :** 08.11.2024  
**Print date :** 05.03.2025

**Version (Revision) :** 7.0.0 (6.0.0)

Remark : Y  
Version : 06.11.2015  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 550 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 275 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000  
ALUMINIUM POWDER (STABILIZED) ; CAS No. : 7429-90-5  
Limit value type (country of origin) : MAK ( CH )  
Parameter : A: respirable fraction  
Limit value : 3 mg/m<sup>3</sup>  
Remark : B  
Version : 22.02.2021  
TALC (MG3H2(SIO3)4) ; CAS No. : 14807-96-6  
Limit value type (country of origin) : MAK ( CH )  
Parameter : A: respirable fraction  
Limit value : 3 mg/m<sup>3</sup>  
Remark : SSC  
Version : 22.02.2021  
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; CAS No. : 64742-48-9  
Limit value type (country of origin) : MAK ( CH )  
Limit value : 300 mg/m<sup>3</sup> / 50 ml/m<sup>3</sup>  
Version : 22.02.2021  
Limit value type (country of origin) : STEL ( CH )  
Limit value : 600 mg/m<sup>3</sup> / 100 ml/m<sup>3</sup>  
Version : 22.02.2021

## Biological limit values

ALUMINIUM POWDER (STABILIZED) ; CAS No. : 7429-90-5  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Aluminium / Urine (U) / At long term exposure: after several previous shifts  
Limit value : 50 µg/g Creatinine  
Version : 25.02.2022

## 8.2 Exposure controls

### Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Personal protection equipment

#### Eye/face protection

Eye glasses with side protection

#### Skin protection

##### Hand protection

Tested protective gloves must be worn Use protective skin cream before handling the product.

##### Body protection

Wear anti-static footwear and clothing Following skin contact Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## 9. Physical and chemical properties

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

## 9.1 Information on basic physical and chemical properties

**Appearance :** Liquid  
**Colour :** Coloured.  
**Odour :** Like solvent.

### Safety characteristics

<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	not applicable
<b>Flash point :</b>		24 °C
<b>Vapour pressure :</b>	( 50 °C )	not applicable
<b>Density :</b>	( 20 °C )	1.2 g/cm <sup>3</sup>
<b>Solvent separation test :</b>	( 20 °C )	< 3 %
<b>Flow time :</b>	( 20 °C )	60 s

DIN-cup 4 mm

## 9.2 Other information

None

## 10. Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

No information available.

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.5 Incompatible materials

Oxidizing agent Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated.

### 10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Acute oral toxicity

Parameter :	LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	14 g/kg
Parameter :	LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Oral
Species :	Rabbit
Effective dose :	7.4 g/kg
Parameter :	LD50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	8500 mg/kg

##### Acute inhalation toxicity

Parameter :	LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Inhalation

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

Species : Rat  
Effective dose : 2000 ppm  
Parameter : LC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 35.7 mg/l

## 11.2 Information on other hazards

### Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Frequently or prolonged contact with skin may cause dermal irritation. The liquid splashed in the eyes may cause irritation and reversible damage. There no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

## 12. Ecological information

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Endocrine disrupting properties

No information available.

### 12.7 Other adverse effects

No information available.

### 12.8 Additional ecotoxicological information

No information available. Do not allow to enter into surface water or drains.

## 13. Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

## 14. Transport information

### 14.1 UN number or ID number

UN 1263

### 14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT

Sea transport (IMDG)

PAINT

Air transport (ICAO-TI / IATA-DGR)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Bilacryl PU D34 / D44  
Revision date : 08.11.2024  
Print date : 05.03.2025

Version (Revision) : 7.0.0 (6.0.0)

PAINT

## 14.3 Transport hazard class(es)

### Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special Provisions : LQ 5 I · E 1 · Transport in containers with max. 450 litres contents are not subject to the regulations of ADR/RID.

Hazard label(s) : 3

### Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-E  
Special Provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 (<= 450 l)  
Hazard label(s) : 3

### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special Provisions : E 1  
Hazard label(s) : 3

## 14.4 Packing group

III

## 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

## 14.6 Special precautions for user

None

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40

#### National regulations

##### Technische Anleitung Luft (TA-Luft) ( D ) :

Weight fraction (Number 5.2.5. I) : < 5 %

##### Water hazard class

Classification according to AwSV - Class ( D ) : 2 (Obviously hazardous to water)

### 15.2 Chemical Safety Assessment

No information available.

## 16. Other information

### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values · 15. Water hazard class

### 16.2 Abbreviations and acronyms

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Bilacryl PU D34 / D44  
**Revision date :** 08.11.2024  
**Print date :** 05.03.2025

**Version (Revision) :** 7.0.0 (6.0.0)

None

## 16.3 Key literature references and sources for data

None

## 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

## 16.6 Training advice

None

## 16.7 Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.