

QualiProtec® Abrasiv B Abrasive Cleaner for coated Surfaces

Product Description

Qualiprotec Abrasiv B has been developed specifically for the QualiProtec Façade Renovation System for the abrasive cleaning of coated surfaces.

Qualiprotec Abrasiv B is particularly suitable for cleaning powder-coated and coated aluminium, as well as high-grade steel elements, synthetics, copper, bronze, chrome and unprotected, anodized and gunmetal-finished aluminium.

Qualiprotec Abrasiv B removes heavy layers of oil, grease and pigment, as well as chalking of metallic surfaces such as high-grade steel, aluminium and organically coated façade elements. QualiProtec Abrasiv B does not affect Eloxal and polyurethane coatings.

Application

Rinse surfaces with clean water to remove loose particles of dirt which could possibly cause damage.

Depending on intensity, heavy soiling and chalking should initially be treated thoroughly with either QualiProtec Cleaner N or QualiProtec Cleaner A using a white façade pad.

The cleaned surface should preferably be kept damp, since this facilitates working with the abrasive cleaner. Apply QualiProtec Abrasiv B undiluted on the areas to be cleaned with a sponge or white façade pad and scrub the surfaces thoroughly.

Then rinse well with clean water to remove all residues of the cleaner. Where there is very hard water, we recommend the use of demineralized water, since calcium residue, trickles and outflow can remain visible when clear coating is applied.

Polish surfaces with a chamois leather cloth, paying particular attention to the edges and ensuring that there are no drips which – when clear coating is applied – would compromise the overall effect.

Do not apply at temperatures below 10 °C, on warm surfaces, or in the blazing sun.

Special Notes

The information contained in this technical data sheet is based on general technical standards and is meant for specialists. Any changes in the recommended operating procedures or specified environmental conditions may significantly influence the results. Our guarantee covers only the quality of the material delivered. We do not undertake any responsibility for the application. In case of doubt, we recommend contacting our Technical Service. Our products are under constant development. Therefore please note date of issue of our technical data sheet and ask for latest edition.

Safety Measures

Avoid contact with skin and eyes. All application and safety measures in the Safety Data Sheet should be observed.

Technical Data

Color	White
Contents	Water-dilutable solution of tensides and abrasives
pH-Value	Neutral
Packaging	Containers of 10 kg
Dilution	Undiluted
Yield	10 – 25 m ² /kg (depending on degree of soiling)
Shelf life	2 years in closed container. Protect from frost.
Waste disposal	QualiProtec Abrasiv B is biodegradable and waste water friendly. However, the local waste water regulations must always be observed.

QualiProtec Abrasiv B	
Flash point	N/A
UN No.	N/A
Danger class RID/ADR	N/A
VOC content	VOC-free

02.12