

QualiProtec® Abrasiv E Abrasive Cleaner for Eloxal

Product Description

Qualiprotec Abrasiv E has been developed specifically for the QualiProtec Façade Renovation System, for the abrasive cleaning of anodized surfaces.

This is an excellent product for removing stubborn stains and crusting on anodized aluminium, copper, brass and chrome. QualiProtec Abrasiv E removes heavy layers of oil, grease and pigment, as well as rust, from metallic surfaces such as high-grade steel and aluminium. QualiProtec Abrasiv E does not affect the Eloxal film of aluminium.

Application

Rinse surfaces with clean water to remove loose particles of dirt which could possibly cause damage.

QualiProtec Abrasiv E can be applied with the red façade pad while surfaces are still damp. Apply product undiluted with a sponge or cleaning pad. Where there is heavy soiling or iridescence, the surfaces can be treated several times with QualiProtec Abrasiv E.

QualiProtec Abrasiv E contains terpene which, if not carefully washed off, can lead to flaws in adhesion of the subsequent coating. Therefore do not allow product to dry and either follow up with QualiProtec Cleaner NE (see Technical Data Sheet) or wash off thoroughly with hot water (> 80 °C).

Do not apply at temperatures below 10 °C, to warm surfaces or in the blazing sun.

Special Notes

The information contained in this technical data sheet is based on general technical standards and is meant for specialists. Any changes in the recommended operating procedures or specified environmental conditions may significantly influence the results. Our guarantee covers only the quality of the material delivered. We do not undertake any responsibility for the application. In case of doubt, we recommend contacting our Technical Service. Our products are under constant development. Therefore please note date of issue of our technical data sheet and ask for latest edition.

Safety Measures

Avoid contact with skin and eyes. All application and safety measures in the Safety Data Sheet should be observed.

Technical Data

Color	Red-brown
Contents	Mixture of tensides and abrasives
pH-Value	Neutral
Packaging	Containers of 10 kg
Dilution	None
Yield	20 – 25 m ² /kg (depending on degree of dirt)
Shelf life	1 year in closed container. Protect from frost.
Waste disposal	QualiProtec Abrasiv E is bio-degradable and waste water friendly. However, the local waste water regulations must always be observed.

	QualiProtec Abrasiv E
Flash point	> 100 °C
UN No.	N/A
Danger class RID/ADR	N/A
VOC value	VOC-free

02.12